



SPECIFICATIONS:

- Windows® 2000 or Windows® XP*
- FTR Gold 2.2 or TheRecord 3.3 or above
- **Operating voltage** 12 VAC, 2 VA maximum. A power jack is provided on the side panel for connecting power. A 120/12 or 240/12 VAC power module with mating connector is included.
- **Input Signal (RS232)** Receives a two-wire RS232 signal from the serial port of the host device. A 1/8" (3.5mm) mono jack is provided on the side panel for connecting the incoming RS232 signal. An optional serial cable with mating plug and DB9 female can be obtained from your vendor.

Note: The Serial connector on your computer may be labeled Serial, RS232 or COM.

- **Input Signal (USB)** Receives a signal from the USB port of the host device. A standard USB connector is provided on the side panel and a suitable USB cable is included.

Note: Windows® 2000 or Windows®XP is required for USB connection.

- **Enclosure** Black, anodized aluminum enclosure with removable rubber feet. Optional mounting brackets are available for bottom, top, and side mount applications. Dimensions: 12"W x 3.5"H x 3.5"D (305mm x 89mm x 89mm).
- **Display** 1.8" (46mm) high, bright red LED, digits. Six digits per side to display hours, minutes and seconds. Discrete LED colons are located between the hours and minutes, as well as between the minutes and seconds. Visible up to 50 feet (15m) away.

**Doesn't apply for connection to a RS232/COM port*

The FTR External USB/Serial Clock Display is a two-sided digital clock that is compatible with both RS232/COM and USB signals and ports. It's preconfigured for a USB connection and includes a USB Cable and USB Driver CD. An optional serial cable is available if connection to a PC serial port is desired.

The FTR External USB/Serial Clock Display produces a large, clearly-visible display of the current record time so court participants are aware that recording is in progress. The time display is also an invaluable tool for participants to note the time of specific events for case review at a later time. The 1.8-inch high digits are visible up to 50 feet away, making the clear hour/minute/second readout easy to see in a small deposition room or a large courtroom.



Versatile Features That Help You Improve Productivity

Convenience

- View recording time from both sides of the display.
- Bright red 1.8-inch (46mm) high digits can be read up to 50 feet (15 meters) away.
- Indicates to all trial or meeting participants that recording is taking place.
- Preconfigured for a USB connection.
- Small 12" x 3.5" (305mm x 89mm) footprint.

Ease of Use

- Six digits per side display time in hours/minutes/seconds (HH:MM:SS).
- Offers participants a way to note times of specific events for use during review.
- Can be connected to RS232/COM port (*requires optional serial cable*)
- Removable rubber feet for tabletop positioning.
- Optional mounting brackets are available for top, bottom or side mounting applications.